




HD 565 ovation

The HD 565 ovation is a top class open dynamic hi-fi stereo headphone. Selected age-resistant materials and the highest degree of precision in manufacturing make the HD 565 ovation a headphone suitable for all types of music. An excellent choice for both studio monitoring and to match top of the range hi-fi systems.

Features


- Extremely lightweight aluminium voice coils ensure excellent transient response
- Radial-bead diaphragm with profile optimised by means of laser interferometry
- Neodymium ferrous magnet system ensures optimum sensitivity and an excellent dynamic response
- Detachable OFC copper cable, very low handling noise

Diffuse Field Frequency Response



Technical Data

Frequency response	16 - 30,000 Hz
Transducer principle	dynamic, open
Frequency characteristic	diffuse field equalised
Nominal impedance	150 Ω
Characteristic SPL at 1 kHz	94 dB
Load rating	200 mW
THD	< 0.15 %
Ear coupling	circumaural
Contact pressure	2.5 N
Weight (without cable)	210 g
Connector	3.5 mm \varnothing stereo mini jack plug with adaptor to 1/4" (6.3 mm) stereo jack plug
Connection cable	3 m, detachable dual-sided OFC copper cable



Recommended Accessories

Stereo volume control HZR 6

Replacement Parts

Ear pads (1 pair) Order no. 50635

Product Variants